

VULCANIZING PRESS



The press in the picture is just an example. It describes the design of the press only.

1. The press is frame type.
2. The diameter of the pistons are $\Phi 750\text{mm}$. We use 2 pistons for this press. The material of the pistons is chilled cast iron. This material has much more advantages, such as much harder surface, much longer working life. The material of cylinders are ductile cast iron. The good material of pistons and cylinders give much more working life.
3. The press is equipped with four (4) pieces of frames, thickness is 70mm each.

PARAMETERS and SPECIFICATIONS

| | |
|---------------------------------|--|
| Model | XLB- DQ2000×1300×2/21.0MN |
| Total pressure(MN) | 21.0 |
| Total working pressure(T) | 2100 |
| Plate size (mm) | 2000×1300×100(middle plate) The upper and the bottom plates are 80mm thick. The material is S45C steel |
| Plate unit pressure(Mpa) | 8.0 |
| Daylight (mm) | 300 |
| Daylight No. | 2 |
| Piston stroke(mm) | 600 |
| Clamping speed (mm/s) | ≥20 |
| Opening speed (mm/s) | ≥20 |
| Hydraulic system pressure (Mpa) | 24.0 |
| Piston dia. (mm) | Φ750 |
| Piston quantity | 2 |
| Motor power (kw) | 11.0×3 |
| Overall size(L×W×H) (mm) | 3200×2000×5200 |
| Weight(kg) | 60000 |

PAYMENT TERMS

1. **FOB Price: USD**
2. Payment terms: 30% paid by T/T as deposit, the balance 70% by irrevocable, transferable, and confirmed L/C.
3. Seaworthy packing
4. Delivery time: within 90 working days after receipt of deposit payment

Origin: PRChina

AFTER SALES SERVICE

We give one year quality guarantee and long-term technical support. We also could train your workers in the factory of the manufacturer. If you need, we could install and assemble the machine in your workshop. A separate offer these jobs will be made on request.

OPTION

Loading system available as option